

WELDING EQUIPMENT AND ACCESSORIES





- 3-in-1 MIG, STICK, TIG
- Integrated Wire feed unit spools up to 15kg or 300mm
 SGT250 Spool Gun compatible
- VRD, Anti-Stick, Hot Start, 2T/4T Trigger Mode, Arc Force (STICK), Down Slope (TIG)
- Digital Amperage and Voltage meters
- Adjustable Burnback and Arc Control
- Fitted with 15 Amp plug
 Fully compliant to AS 60974.1-2006. Enclosure rated to IP23S Designed for indoor & outdoor use.
- 3 Year limited warranty

Transmig 255i Inverter Power Source 27kg • Tweco Professional Fusion 250 CONTENTS MIG Torch 3m • COMET Professional Argon Regulator / Flowmeter* • Feedrolls: 0.9/1.2mm "V" groove (fitted), 0.6/0.8mm "V" groove, 0.9/1.0mm (U) groove, 0.8/0.9mm "V" knurled • Contact Tips: 0.9mm (fitted) 0.8mm, 0.9mm, 1.0mm • Twistlock Electrode Holder with 4m Lead • Work Clamp with 4m Lead • Shielding Gas Hose Assembly • Operating Manual

Multi-Process Inverter Plant (with 4RT Wirefeeder)

P/N: W1005350

- Full multi process capabilities: MIG (GMAW / FCAW), Stick (MMAW), Lift TIG (GTAW) Standards Compliant (VRD)
- Fully Complies to AS 60974.1 & AS 1674
- Digital Voltage and Amperage Meters
 Fully enclosed 4RT wirefeeder
- Enclosure rated to IP23S
- Fan on demand

MIG

TIG

STICK

- Welding setup program storage (10 programs)
 3 Year Limited Warranty



Transmig 350i Power source • Transmig 4RT Wirefeeder • 8m Interconnection Lead 10pin • Tweco Professional No.4 MIG Torch • Comet Prof, Argon Reg/Flowmeter • 0.9-1.2 V Groove Feed Roll fitted • Electrode holder & Work Clamp with 5m Lead • Trolley • Operating Manual



3 VEARS*

עהיע PFC





PART NUMBER	MODEL	240V PLUG SIZE	PFC & IP23S	STICK DEADMAN Switch	STICK (VRD)	LIFT TIG	HF TIG	PULSE	BRAIDED LEAD & IP66 Supply plug
W1007130	Transarc 130i Plant	10A	\checkmark		\checkmark	\checkmark			
W1007131	Transarc 130i Plant (Mine Spec)	10A	\checkmark	\checkmark	\checkmark	\checkmark			✓
W1007170	Transarc 170i Plant	15A	\checkmark		\checkmark	\checkmark			
W1007171	Transarc 170i Plant (Mine Spec)	15A	\checkmark	✓	✓	\checkmark			~
W1007190	Transtig 170Pi Plant	15A	\checkmark		\checkmark	\checkmark	\checkmark	\checkmark	

TWECO

TWECO No.4 MIG Gun

EQUIPMENT

P/N: 717201 • P/N: 0TWX412/3545

- Heavy duty design
- High impact resistant
- handle & components
- Large range of consumables available
- Metal jacketed conductor tube
- Oval handle shape reduces operator fatigue

PART NUMBER | LENGTH | CONNECTION TYPE 717201 Tweco No.4 3.6m OTWX412/3545 3.6m Euro OTWM412/3545 3.6m Mille OTWL415-116 4.5m Lincolr

Our genuine Tweco **Professional Series MIG Torch range** delivers quality products that exceed expectations.

TWECO Flexible Conductor Tubes



TWECO Consumables

Tweco Contact Tips

- P/N: 0TW14/35
- 0.9mm
- Pkt Qty: 25
- Available in various sizes





- P/N: 0TW24A/62
- Pkt Qty: 2
- · Available in various sizes



P/N: 0TW54A • Pkt Qty: 5

Tweco Gas

Diffusers

• Complete range available



Tweco Conduit Liners P/N: 0TW44/3545

- 4.5m 0.9-1.2mm Hard Tweco No. 4
- Complete range available

TWECO Organiser

MIG Torch Consumables Organiser P/N: W4012300

INCLUDES

- WSPLIER Tweco WeldSkill MIG Pliers (x1)
- **OTW32** Tweco Insulator (x2)
- OTW22/50 Tweco Nozzle Adjustable 13mm (x2)
- OTW52 Tweco Gas Diffuser Tweco (x2)
- OTW14/30 Contact Tip 0.8mm Tweco (x10)
- 0TW14/35 Contact Tip 0.9mm (x10)



- TWECO Fusion 150 P/N: W4013701
- Tweco Fusion 250 3.0M P/N: W401370
- Tweco Fusion 250 3.6M P/N: OTWF212X3035 Weldskill 250 MIG
- Tweco SGT250 Spool Gun P/N: W4011250

• Transmig 175i+/220i/250i/255i

Rebel EMP 215ic

• Transmig 185 Ultra

• Rebel EMP 235ic.

THE IDEAL COMPANION FOR MIG WELDERS



TWECO Electrode Holder

P/N: 646142

- Complies to AS60974.11
- Electrode capacity from 1.6mm to 6.35mm
- Fully insulated
- Accepts 50mm² to 70mm² welding cable
- 400A @ 35%, 300A @ 60% Duty Cycle

Also available in a 250Amp version Part No. 646165





TWECO SGT250 Spool Gun

P/N: W4011250

- 6m Lead with Euro Connection
- Argon Duty Cycle: 250A@20% • Wire feed viewing window

• Adjustable pressure roll tensior

WELDING EQUIPMENT



WeldSkill 200HF Inverter

P/N: W1008200

- 15 Amp Single Phase
- Pulse TIG in DC TIG Welding
- STICK with VRD, Anti-Stick & Hot Start
- Up/Down Slope
- Pre/Post Flow
- 2T/4T Trigger Function
- Spot Mode
- Gas Purge for DC TIG Welding
- Width and Peak Current adjustability

0 18 110 TIG STICK 001 WeldSkill 200HF Inverter Power Source • TIG Torch type 26F with flex head, 4m lead,

trigger switch and remote current control • TIG Torch Accessory Kit • WeldSkill Argon Regulator/Flowmeter • 4m Lead with Twistlock Electrode Holder • 4m Lead with Work Clamp • Shielding Gas Hose Assembly • Shoulder Strap

1.2mm • Shielding Gas Hose Assembly • Wheeling kit & operation manual

WeldSkill 135

Dual Process Welding Inverter P/N: W1008135

- MIG Suitable for Gas & Gasless wires up to 0.9mm
- Capable of MIG welding mild steel up to 4mm
- STICK Suitable for up to 3.2mm electrodes
- Plug & Play Runs on any 10amp power point
- Designed specifically for the home handyman / tradesman
- 1 Year Warranty

WeldSkill 135 Power Source 12.8kg* • H-180G MIG Torch 2.5m - Hardwired • Work Clamp with 3m Lead - Hardwired • Electrode Holder with 3m Lead • Shielding Gas Hose Assembly, 3m • Feed Rolls: 0.8/0.9mm Flux Cored (Fitted), 0.6/0.8mm V Groove • Contact Tip: 0.8mm (Fitted)

WeldSkill 140 / 180 Inverter

P/N: W1008140 • P/N: W1008180

user-friendly control panel, practical push button operation for mode selection, clearly visible LED indicators and sturdy large control knob

- Twist lock electrode holder 3 Year Warranty
- Rugged case with carry handle and carry strap
- 4m long electrode holder and work leads
- Push button weld mode selection switch with LED indicators

CONTENTS strap • Operating manual



4m Long Electrode Holder & Work Leads • Rugged case with carry handle and carry

WeldSkill 205 AC/DC Plant

- P/N: W1008205
- 15 Amp Single Phase
- Pulse TIG in both AC & DC TIG Welding
- High Frequency AC/DC



WeldSkill 205AC/DC HF TIG Inverter Power Source • TIG Torch with 8m Lead and Remote Control • TIG Torch Accessory Kit • CutSkill Preset Argon Regulator/ Flowmeter • Twistlock Electrode Holder with 4m Lead • Work Clamp with 4m Lead Shoulder Strap

WeldSkill 155 / 185 Inverter

P/N: W1008155 • P/N: W1008185

- MIG, STICK, TIG Welding Inverter
- Plug & Play runs on any 10am
- Digital Amperage and Voltage M
- SGT250 Spool Gun Compatible

2 Year Warranty

WeldSkill Power Source 13.7kg • MIG Torch with Euro Connection 3m • Twistlock Electrode Holder with 3m Lead • CutSkill Argon Regulator/Flowmeter • Work Clamp with 3m Lead • Shielding Gas Hose Assembly • 3m, Feed Rolls: 0.8/0.9mm Flux Cored (Fitted) • 0.8/0.9mm V Groove • Contact Tip: 0.8mm (Fitted)

WeldSkill 180 Tradepack

P/N: W1008181

- Twist lock electrode holder
- 3 Year Warranty
- Rugged case with carry
- handle and carry strap • 4m long electrode holder and work leads
- Push button weld mode selector with LED indicators

TIG



Bag • WeldSkill Helmet Blue • Welding Gloves • Chipping Hammer • Wire Brush • **CONTENTS** 1kg Electrodes • Operating manual.

> 0 f У 🕨 CIGWELD.COM.AU



(ICWFI







MIG STICK TIG

Safety

WELDING HELMETS

WeldSkill Auto-Darkening Helmets

CIGWELD WeldSkill Welding Helmets are specifically designed for the budget conscious welder and offer excellent

- Fit for purpose
- Auto Darkening
- Medium Impact Rating
- Optional Magnification Lens
- Complies to AS1337:1992 and AS1338.1:1992



2



2 VEARS*

Spider P/N: 454343

Barbed Wire P/N: 454352

Blue P/N: 454350

Pro Racer P/N: 454353



MIG STICK

TIG PLASMA

WeldSkill Welding Jacket Blue/Black

Medium P/N: 646771 • Large P/N: 646772 XLarge P/N: 646773 • XXLarge P/N: 646774

- Light weight flame resistant cotton jacket offering the perfect protection for Arc Welding
- Insulated and dielectric press studs
- Flame Resistant Kevlar Stitching
- ultimate fit and spark protection • Roll Up Collar with adjustable press studs for ultimate fit and spark protection
- Adjustable press stud waist for
- greater comfort and fit • Fully Washable material
- Two convenient inside pockets

WeldSkill Magnetic Clamp

Medium P/N: 646764 • Large P/N: 646765

- Multi-Angle Allows you multiple positions to hold your metal work pieces in place while welding.
- Medium 92mm, Large 112mm • Arrow Shape Gives you the flexibility of 3 common holding angles: 45° / 90° / 135°
- Strong Magnetic Hold This strong magnet secures ferrous metals (such as steel) in place - allowing you to keep both your hands free for welding accuracy
- Holding Capacity Medium: 22kg, Large: 34kg
- Durability These holders are highly durable
- and made of heavy duty construction for years of use.
- Ideal for use with Mild Steel Welding, Soldering, Assembly, Pipe installation, Marking off, Floater, and in Hanging Applications etc.



COMING

SOON

Weldskill Welding Curtains

Red 1.8m x 1.8m P/N: 646777 Dark Green 1.8m x 1.8m P/N: 646770 Frame (optional) P/N: 646776

- DARK GREEN Low Transparency, High UV and blue light resistance • RED – Moderate Transparency,
- Moderate UV resistance • Protects against exposure to flame,
- spatter and molten splash • Kevlar stitched
- Brass grommets around edges
- for easy attachment to frames



WeldSkill Welding Gloves

WeldSkill Heavy Duty **Leather Welding Gloves** Medium P/N: 646766 • Large P/N: 646755 XLarge P/N: 646767



WeldSkill Leather **TIG Welding Gloves** Medium P/N: 646768 Large P/N: 646754 XLarge P/N: 646769



WE'VE GOT WELDING & CUTTING COVERED



• Includes Stainless Steel Curtain Rings



Thermal Dynamics Cutmaster range fitted with the proven 1 Torch

10mm | 12mm | 20mm | 25mm | 35mm | 40mm

Cutmaster 12mm

Manual Plasma

P/N: 1-4200-6

3

PFC

The Cutmaster 12mm manual plasma is an inverter based system specifically designed to provide excellent cutting and bevelling performance on materials up to 12mm thick.

- 1 phase, 50/60Hz 15A input plug fitted; **Power Factor Correction**
- Maximum Output Current 40 amps
- Cycle (@ 40°C) 40A @ 40%
- Warranty Power Source 3 Years;
- Minimum Recommended Generator 5kVA
- Torch 1 Year*

Cutmaster 40mm

Manual Plasma

P/N: 1-1930-4

The Cutmaster 40mm manual plasma the largest air cooled system in the range, designed for high level applications requiring superior endurance and cutting performance.

- Supply Voltage 415 volt (+/- 15%), 3 phase, 50/60Hz
- Minimum Recommended Generator 23kVA

PFC ONLY ON 10MM, 12MM MODELS ONLY

• Maximum Output Current 120 amps

3

PFC

- Duty Cycle (@ 40°C) 120A @ 80%
- Warranty Power Source 3 Years; Torch 1 Year*

PLASMA



Manual Plasma Technical Specifications

	•					
	CUTMASTER 10MM	CUTMASTER 12MM	CUTMASTER 20MM	CUTMASTER 25MM	CUTMASTER 35MM	CUTMASTER 40MM
PART NO.	1-4730-6	1-4200-6	1-1130-4 — Aust. & NZ	1-1330-4 — Aust. & NZ	1-1730-4 – Aust. & NZ	1-1930-4 — Aust. & NZ
CUTTING DATA	Genuine 10mm – Severance 12mm Pierce 5mm	Genuine 12mm – Severance 15mm Pierce 6mm	Genuine 20mm Maximum 25mm Severance 32mm Pierce 12mm	Genuine 25mm Maximum 30mm Severance 38mm Pierce 15mm	Genuine 35mm Maximum 40mm Severance 45mm Pierce 20mm	Genuine 40mm Maximum 50mm Severance 55mm Pierce 25mm
OUTPUT CURRENT	20-30 Amps, Adjustable	20-40 Amps, Adjustable	20 — 60 Amps, Adjustable	20 — 80 Amps, Adjustable	25 -100 Amps, Adjustable	25 -120 Amps, Adjustable
INPUT POWER	240V, 1 Phase, 50/60 Hz, 10 Amps	240V, 1 Phase, 50/60 Hz, 15 Amps	415V, 3 Phase, 50/60 Hz, 16 Amps	415V, 3 Phase, 50/60 Hz, 20 Amps	415V, 3 Phase, 50/60 Hz, 27 Amps	415V, 3 Phase, 50/60 Hz, 32 Amps
MINIMUM RECOMMENDED Generator	3.8kVA	5kVA	12kVA	15kVA	20kVA	23kVA
INPUT POWER CABLE	3m with 10 Amp Plug	3m with 15 Amp Plug	2m without Plug	2m without Plug	2m without plug	2m without plug
WORK CABLE	6.1m	6.1m	6.1m	6.1m	6.1m	6.1m
DUTY CYCLE	30A @ 40%	40A @ 40%	60A @ 40%	80A @ 40%	100A @ 80%	120A @ 80%
DIMENSIONS	Length 490mm Width 175mm Height 300mm	Length 490mm Width 175mm Height 300mm	Length 615mm Width 315mm Height 385mm	Length 615mm Width 315mm Height 385mm	Length 775mm Width 315mm Height 385mm	Length 775mm Width 315mm Height 385mm
WEIGHT (POWER SOURCE)	14 kg	14 kg	19.5 kg	19.5 kg	28.1 kg	28.1 kg

PLASMA



Plasma

MANUAL PLASMA CUTTING SYSTEMS

CutSkill

ACETYLENE & LPG GAS CUTTING & WELDING KITS

CutSkill Tradesman Plus LPG

Gas Cutting & Welding Kit P/N: 208021

Economical way for light to medium, brazing, cutting and heating applications.

Portable and light with a heavy duty brass construction, the CIGWELD CutSkill Tradesman Plus LPG Kit offers an excellent and economical ready to go package.

Oxygen Regulator: 800kPa • LPG Regulator: 400kPa • Blowpipe Cutting Attachment • Mixer • Regulator Flashback Arrestors x 2 • Blowpipe Flashback Arrestors x 2 • Twin Welding Hose 5m • Welding Tip: Size 15 • Cutting Nozzles: Size 8, 12, 15 • Heating Nozzle 20x9 HT • Welding Goggles • Flint Lighter • Combination Spanner • Tip Cleaners • Heavy Duty Toolbox

IDEAL FOR Tradesman, contractor & handyman

CutSkill Tradesman Plus

Gas Cutting & Welding Kit P/N: 208007

The CutSkill Tradesman PLUS gas cutting and welding kit has been designed for general purpose oxygen - acetylene cutting and welding applications.



CutSkill Oxygen Regulator: 800kPa • CutSkill Acetylene Regulator: 150kPa • CutSkill Blowpipe • CutSkill Cutting Attachment • CutSkill Mixer • Regulator Flashback Arrestors x 2 • Blowpipe Flashback Arrestors x 2 • Twin Welding Hose 10m • Welding Tips: 8/12/15 • Cutting Nozzles: 8/12/15 • Heating Tip 8x12 HT

- Lift Front Welding Goggles Roller Guide and Radius Bar Flint Lighter
- Combination Spanner
 Tip Cleaners
 Heavy Duty Steel Toolbox

IDEAL FOR Tradesman, contractor & handyman

CutSkill Tradesman IPG

Gas Cutting & Welding Kit P/N: 208011

The CutSkill Tradesman gas cutting and welding kit has been designed for general purpose oxygen – LPG cutting and welding applications.



Oxygen Regulator • LPG Regulator • Oxy/LPG Gas Hose 5m • Blowpipe Cutting Attachment - Mixer © Cutting Nozle Size 8, 12 and 15
 Welding Tip Size 15 © Goggles - Standard © Combination Spanner
 Tip Cleaner © Flint Lighter © Heavy Duty Toolbox

ACETYLENE

IDEAL FOR Tradesman, contractor & handyman

CutSkill Tradesman

Gas Cutting & Welding Kit P/N: 208001

The CutSkill Tradesman gas cutting and welding kit has been designed for general purpose oxygen acetylene cutting and welding applications.



Oxygen Regulator • Acetylene Regulator • Oxy/Acetylene Gas Hose 5m • Blowpipe • Cutting Attachment • Mixer • Cutting Nozzle Size 8, 12 and 15 • Welding Tip Size 8 • Welding Tip Size 12 • Welding Tip Size 15 • Goggles - Standard • Combination Spanner • Tip Cleaner

- Flint Lighter
 Heavy Duty Toolbox









CutSkill

CUTSKILL GAS EQUIPMENT

CutSkill Blowpipe & Cutting Attachment


Blowpipe P/N: 204001 Cutting Attachment P/N: 204005

- Cuts up to 150mm (6")
- Locking teeth provides secure positioning
- For use with Type 41 & 44 cutting nozzles
- Solid brass construction
- Blowpipe handle shape gives
- comfortable positive grip.
- Colour coded control knobs

IDEAL The CutSkill Blowpipe & Cutting Attachment is ideal for the tradesman, contractor and handyman. The multi-fuel mixer designed for use with Oxy/Acetylene, Oxy/LPG & Oxy/ Natural Gas

CutSkill Cutting Nozzles TYPE 41 / 44

Type 41 nozzles are manufactured from copper that provides effective heat resistance and the Type 44 are of a two-piece construction incorporating a copper shroud.



CutSkill Regulators

IDEAL Use with Oxy/Acet & Oxy/LPG. 2 Seat Design.

- Regulator is failsafe against over pressure
- Robust, failsafe and accurate pressure gauges
- Captive control knob prevents loss and tampering
- Colour coding for gas identification

Regulator Flowmeters

30 lpm Vertical Inlet: P/N: 201030 30 lpm Side Inlet: P/N: 201031 The Regulator/Flowmeters have been designed for TIG processes and for MIG, Short Arc and Spray Arc applications and are calibrated for 0 to 30 lpm.

15 LPM: P/N: 201710 (TIG) 40 LPM: P/N: 201711 (MIG)

Suit 201021(VI) or 201024 (SI) CutSkill Preset Argon Regulator. The 201710 Flowmeter has been designed for TIG processes and is calibrated for 1 to 15 lpm. The metering bobbin is a Teflon ball. The 201711 Flowmeter has been designed for MIG, Short Arc and Spray Arc applications and is calibrated for 10 to 40 lpm. The metering bobbin is stainless steel.

CutSkill Flashback Arrestors

Regulator Set: P/N: 208504 Blowpipe Set: P/N: 208505

- Available in both Regulator mounted and Blowpipe mounted variants for Oxygen and Fuel
- Stainless Steel flame arrestor
- Non-return valve
- Complies to AS4603
- Sold in pairs:
- Blowpipe set Oxy and Fuel included
 Maximum working pressures:
- Fuel Acetylene 150 kPa, LPG 400 kPa
- Oxygen 800 kPa





Specifically designed for the budget conscious buyer, CutSkill regulators offer excellent quality and performance for use with most light to medium applications.

COMET Edge



- Better flow control across a full range of cylinder pressures
- Exceptional sensitivity and precision in delivery pressure control
- Outlet hose connection points away from the user
- High and low pressure gauges are recessed into the body and protected by a built-in gauge guard.
- High-strength diaphragm assembly

Cutting Edge Performance! "



PACKAGE 1 x Comet Platecutter • 3.6 metres of track • 1 x Comet Type 41 High Speed CONTENTS Cutting Nozzle – Size 8 • 1 x Tip cleaner set • 2 x Spanners

☑ If ♥ ■ CIGWELD.COM.AU



WE RECOMMEND GENUINE CIGWELD PRODUCTS



THE BIGGEST RANGE AND THE BEST QUALITY, WITH GUARANTEED PERFORMANCE.

ESAB *

CIGWELD Pty Ltd An ESAB Brand 71 Gower Street, Preston VIC 3072 Australia Customer Care: Tel: 1300 654 674 Fax: 03 9474 7391 | Email: enquiries@cigweld.com.au International Enquiries: Tel: +61 3 9474 7508 Fax: +61 3 9474 7488

🖸 🖪 🎔 🖻 🛛 CIGWELD.COM.AU

In the interest of continuous improvements, CIGWELD Pty Ltd ABN 56 007 226 815 (An ESAB Brand) reserves the right to change specifications or design on any of its products without prior notice.