



AN ESAB BRAND

CIGWELD Comcoat C

Cigweld Pty Ltd

Chemwatch: 16375

Version No: 7.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 23/12/2022

Print Date: 31/01/2023

L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| | |
|-------------------------------|--|
| Product name | CIGWELD Comcoat C |
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Chemical formula | Not Applicable |
| Other means of identification | 321186, 321191, 322020, 322021, 322206 |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|--------------------------|--|
| Relevant identified uses | Flux coated manganese bronze filler rod for oxy-acetylene gas flame braze welding of steel, cast iron malleable iron, etc. Extensively used in the automotive and maintenance industry. |
|--------------------------|--|

Details of the manufacturer or supplier of the safety data sheet

| | |
|-------------------------|--|
| Registered company name | Cigweld Pty Ltd |
| Address | 71 Gower Street Victoria 3072 Australia |
| Telephone | +613 9474 7400 +1 1300 654 674 |
| Fax | Not Available |
| Website | www.cigweld.com.au |
| Email | Not Available |

Emergency telephone number

| | |
|-----------------------------------|---------------|
| Association / Organisation | Not Available |
| Emergency telephone numbers | Not Available |
| Other emergency telephone numbers | Not Available |




SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Chemwatch Hazard Ratings

CIGWELD Comcoat C

| | Min | Max |
|--------------|-----|---|
| Flammability | 0 | |
| Toxicity | 2 |  |
| Body Contact | 1 |  |
| Reactivity | 0 | |
| Chronic | 4 |  |

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

| | |
|---------------------------|--|
| Poisons Schedule | Not Applicable |
| Classification [1] | Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Inhalation) Category 4, Carcinogenicity Category 1A, Hazardous to the Aquatic Environment Acute Hazard Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 1 |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

| | |
|----------------------------|---|
| Hazard pictogram(s) |  |
| Signal word | Danger |

Hazard statement(s)

| | |
|-------------|---|
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H350 | May cause cancer. |
| H402 | Harmful to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

Precautionary statement(s) Prevention

| | |
|-------------|--|
| P201 | Obtain special instructions before use. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
| P261 | Avoid breathing dust/fumes. |

Precautionary statement(s) Response

| | |
|-----------------------|--|
| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |

Precautionary statement(s) Storage

| | |
|-------------|------------------|
| P405 | Store locked up. |
|-------------|------------------|

Precautionary statement(s) Disposal

| | |
|-------------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|-------------|--|

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|---------------|-----------|-----------------|
| Not Available | | wire comprising |

CIGWELD Comcoat C

| CAS No | %[weight] | Name |
|---|-----------|-----------------------------|
| 7440-50-8 | 58 | <u>copper</u> |
| 7440-66-6 | 41 | <u>zinc</u> |
| 7440-31-5 | 1 | <u>tin</u> |
| Not Available | | coated with flux containing |
| 10043-35-3 | | <u>boric acid</u> |
| 7775-19-1 | | <u>sodium metaborate</u> |
| Not Available | | in use generates |
| Not Available | >60 | <u>welding fumes</u> |
| Not Available | | including |
| 7440-50-8. | | <u>copper fume</u> |
| 1314-13-2 | | <u>zinc oxide fume</u> |
| 7439-96-5. | | <u>manganese fume</u> |
| 7440-31-5 | | <u>tin fume</u> |
| Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available | | |

SECTION 4 First aid measures

Description of first aid measures

| | |
|---------------------|---|
| Eye Contact | <ul style="list-style-type: none"> Particulate bodies from welding spatter may be removed carefully. DO NOT attempt to remove particles attached to or embedded in eye. Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye. Seek urgent medical assistance, or transport to hospital. |
| Skin Contact | In case of burns: <ul style="list-style-type: none"> Quickly immerse affected area in cold running water for 10 to 15 minutes. Bandage lightly with a sterile dressing. Treat for shock if required. Lay patient down. Keep warm and rested. Transport to hospital, or doctor. |
| Inhalation | <ul style="list-style-type: none"> If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. |
| Ingestion | Not normally a hazard due to the physical form of product. The material is a physical irritant to the gastro-intestinal tract |

Indication of any immediate medical attention and special treatment needed

Copper, magnesium, aluminium, antimony, iron, manganese, nickel, zinc (and their compounds) in welding, brazing, galvanising or smelting operations all give rise to thermally produced particulates of smaller dimension than may be produced if the metals are divided mechanically. Where insufficient ventilation or respiratory protection is available these particulates may produce "metal fume fever" in workers from an acute or long term exposure.

- Onset occurs in 4-6 hours generally on the evening following exposure. Tolerance develops in workers but may be lost over the weekend. (Monday Morning Fever)
- Pulmonary function tests may indicate reduced lung volumes, small airway obstruction and decreased carbon monoxide diffusing capacity but these abnormalities resolve after several months.
- Although mildly elevated urinary levels of heavy metal may occur they do not correlate with clinical effects.
- The general approach to treatment is recognition of the disease, supportive care and prevention of exposure.
- Seriously symptomatic patients should receive chest x-rays, have arterial blood gases determined and be observed for the development of tracheobronchitis and pulmonary edema.

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.

Continued...

CIGWELD Comcoat C

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|---|
| Fire Incompatibility | Welding electrodes should not be allowed to come into contact with strong acids or other substances which are corrosive to metals. Welding arc and metal sparks can ignite combustibles. |
|-----------------------------|---|

Advice for firefighters

| | |
|------------------------------|---|
| Fire Fighting | <ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. |
| Fire/Explosion Hazard | <ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk, however containers may burn. ▶ In a fire may decompose on heating and produce toxic / corrosive fumes. |
| HAZCHEM | Not Applicable |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|---|
| Minor Spills | Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety glasses. Use dry clean up procedures and avoid generating dust. Place spilled material in clean, dry, sealable, labelled container. |
| Major Spills | Minor hazard. <ul style="list-style-type: none"> ▶ Clear area of personnel. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Control personal contact with the substance, by using protective equipment if risk of overexposure exists. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

| | |
|--------------------------|--|
| Safe handling | <ul style="list-style-type: none"> ▶ Limit all unnecessary personal contact. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Avoid contact with incompatible materials. |
| Other information | <ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. |

Conditions for safe storage, including any incompatibilities

| | |
|--------------------------------|---|
| Suitable container | <ul style="list-style-type: none"> ▶ Packaging as recommended by manufacturer. ▶ Check that containers are clearly labelled Multi-wall paper container NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. |
| Storage incompatibility | Segregate from strong acids and strong oxidisers |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|-----------------|--|-----------|---------------|---------------|--|
| Australia Exposure Standards | copper | Copper, dusts & mists (as Cu) | 1 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | copper | Copper (fume) | 0.2 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | tin | Tin, metal | 2 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | welding fumes | Welding fumes (not otherwise classified) | 5 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | copper fume | Copper (fume) | 0.2 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | copper fume | Copper, dusts & mists (as Cu) | 1 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | zinc oxide fume | Zinc oxide (dust) | 10 mg/m3 | Not Available | Not Available | (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica. |
| Australia Exposure Standards | zinc oxide fume | Zinc oxide (fume) | 5 mg/m3 | 10 mg/m3 | Not Available | Not Available |
| Australia Exposure Standards | manganese fume | Manganese, fume (as Mn) | 1 mg/m3 | 3 mg/m3 | Not Available | Not Available |
| Australia Exposure Standards | tin fume | Tin, metal | 2 mg/m3 | Not Available | Not Available | Not Available |

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
|-------------------|-----------|----------|-------------|
| copper | 3 mg/m3 | 33 mg/m3 | 200 mg/m3 |
| zinc | 6 mg/m3 | 21 mg/m3 | 120 mg/m3 |
| tin | 6 mg/m3 | 67 mg/m3 | 400 mg/m3 |
| boric acid | 6 mg/m3 | 23 mg/m3 | 830 mg/m3 |
| sodium metaborate | 6.8 mg/m3 | 77 mg/m3 | 460 mg/m3 |
| copper fume | 3 mg/m3 | 33 mg/m3 | 200 mg/m3 |
| zinc oxide fume | 10 mg/m3 | 15 mg/m3 | 2,500 mg/m3 |
| manganese fume | 3 mg/m3 | 5 mg/m3 | 1,800 mg/m3 |
| tin fume | 6 mg/m3 | 67 mg/m3 | 400 mg/m3 |

| Ingredient | Original IDLH | Revised IDLH |
|-------------------|---------------|---------------|
| copper | 100 mg/m3 | Not Available |
| zinc | Not Available | Not Available |
| tin | Not Available | Not Available |
| boric acid | Not Available | Not Available |
| sodium metaborate | Not Available | Not Available |
| welding fumes | Not Available | Not Available |
| copper fume | 100 mg/m3 | Not Available |
| zinc oxide fume | 500 mg/m3 | Not Available |
| manganese fume | 500 mg/m3 | Not Available |
| tin fume | Not Available | Not Available |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|------------|-----------------------------------|----------------------------------|
| boric acid | D | > 0.01 to ≤ 0.1 mg/m³ |

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.


CIGWELD Comcoat C

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|-------------------|--|----------------------------------|
| sodium metaborate | E | ≤ 0.01 mg/m ³ |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. | |

MATERIAL DATA

None assigned. Refer to individual constituents.

Exposure controls

| | |
|---|--|
| Appropriate engineering controls | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p> <p>If risk of inhalation or overexposure exists, wear SAA approved respirator or work in fume hood.</p> |
| Personal protection |  |
| Eye and face protection | <p>Welding helmet with suitable filter. Welding hand shield with suitable filter.</p> <ul style="list-style-type: none"> ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. ▶ Goggles or other suitable eye protection shall be used during all gas welding or oxygen cutting operations. Spectacles without side shields, with suitable filter lenses are permitted for use during gas welding operations on light work, for torch brazing or for inspection. ▶ For most open welding/brazing operations, goggles, even with appropriate filters, will not afford sufficient facial protection for operators. Where possible use welding helmets or handshields corresponding to EN 175, ANSI Z49:12005, AS 1336 and AS 1338 which provide the maximum possible facial protection from flying particles and fragments. |
| Skin protection | See Hand protection below |
| Hands/feet protection | <p>Welding Gloves</p> <p>Safety footwear</p> |
| Body protection | See Other protection below |
| Other protection | <p>Overalls</p> <ul style="list-style-type: none"> ▶ Eyewash unit. <p>Aprons, sleeves, shoulder covers, leggings or spats of pliable flame resistant leather or other suitable materials may also be required in positions where these areas of the body will encounter hot metal.</p> |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the

computer-generated selection:

CIGWELD Comcoat C

| Material | CPI |
|----------|-----|
| BUTYL | A |
| NEOPRENE | A |
| NITRILE | A |
| VITON | A |

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis,

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | -AUS P2 | - | -PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | -AUS / Class 1 P2 | - |
| up to 100 x ES | - | -2 P2 | -PAPR-2 P2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling

Continued...

factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| | | | |
|---|---|--|----------------|
| Appearance | Pale blue flux-coated wire; insoluble in water. | | |
| Physical state | Manufactured | Relative density (Water = 1) | 6.7 |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Applicable |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | 900 | Viscosity (cSt) | Not Applicable |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Applicable | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Applicable |
| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
| Solubility in water | Immiscible | pH as a solution (1%) | Not Applicable |
| Vapour density (Air = 1) | Not Applicable | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| | |
|---|--|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| | |
|----------------|---|
| Inhaled | <p>Fumes evolved during welding operations may be irritating to the upper-respiratory tract and may be harmful if inhaled. Copper poisoning following exposure to copper dusts and fume may result in headache, cold sweat and weak pulse. Capillary, kidney, liver and brain damage are the longer term manifestations of such poisoning. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever". Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Inhalation of freshly formed zinc oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever", with symptoms resembling influenza. Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalised feeling of malaise. Mild to severe headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhoea, excessive urination and prostration may also occur.</p> <p>Manganese fume is toxic and produces nervous system effects characterised by tiredness. Acute poisoning is rare although acute inflammation of the lungs may occur. A chemical pneumonia may also result from frequent exposure. Inhalation of freshly</p> |
|----------------|---|

CIGWELD Comcoat C

| | |
|---------------------|---|
| | <p>formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever".</p> <p>Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.</p> <p>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.</p> |
| Ingestion | Not normally a hazard due to physical form of product. |
| Skin Contact | <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>The material may accentuate any pre-existing skin condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> |
| Eye | Fumes from welding/brazing operations may be irritating to the eyes. |
| Chronic | <p>Principal routes of exposure include accidental contact with the molten metal and inhalation of fume arising as a consequence of the action of the flame on the rod / wire. Although fume generation rates are generally low, excessive heating of the material, well above its quoted melting point, may result in over-exposure.</p> <p>severe disorders of the nervous system, has been reported in welders working on Mn steels in confined spaces.</p> |

| | | |
|--------------------------|--|--|
| CIGWELD Comcoat C | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| copper | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation(Rat) LC50: 0.733 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Mouse) LD50; 0.7 mg/kg ^[2] | |
| zinc | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 1130 mg/kg ^[2] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: >2000 mg/kg ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| tin | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation(Rat) LC50: >4.75 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: >2000 mg/kg ^[1] | |
| boric acid | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >2000 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation(Rat) LC50: >2.12 mg/l4h ^[1] | Skin (human): 15 mg/3d -I- mild |
| | Oral (Rat) LD50: >2600 mg/kg ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| sodium metaborate | TOXICITY | IRRITATION |
| | dermal (guinea pig) LD50: >2000 mg/kg ^[2] | Not Available |
| | Inhalation(Rat) LC50: >2.03 mg/l4h ^[1] | |
| | Oral (Rat) LD50: >250 mg/kg ^[1] | |
| welding fumes | TOXICITY | IRRITATION |
| | Not Available | Not Available |
| copper fume | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation(Rat) LC50: 0.733 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Mouse) LD50; 0.7 mg/kg ^[2] | |
| zinc oxide fume | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye (rabbit): 500 mg/24h mild |
| | Inhalation(Rat) LC50: >1.79 mg/l4h ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |

| | | |
|----------------|---|--|
| | Oral (Rat) LD50: >5000 mg/kg ^[1] | Skin (rabbit): 500 mg/24h mild |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| manganese fume | TOXICITY | IRRITATION |
| | Inhalation(Rat) LC50: >5.14 mg/l4h ^[1] | Eye (rabbit) 500mg/24H Mild |
| | Oral (Rat) LD50: >2000 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | | Skin (rabbit) 500mg/24H Mild |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| tin fume | TOXICITY | IRRITATION |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye: no adverse effect observed (not irritating) ^[1] |
| | Inhalation(Rat) LC50: >4.75 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: >2000 mg/kg ^[1] | |
| Legend: | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | |

| | |
|--|--|
| COPPER | <p>WARNING: Inhalation of high concentrations of copper fume may cause "metal fume fever", an acute industrial disease of short duration. Symptoms are tiredness, influenza like respiratory tract irritation with fever.</p> <p>The following information refers to contact allergens as a group and may not be specific to this product.</p> <p>Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.</p> <p>for copper and its compounds (typically copper chloride):</p> <p>Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw.</p> |
| SODIUM METABORATE | <p>anhydrous: for octahydrate</p> <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.</p> |
| WELDING FUMES | <p>Most welding is performed using electric arc processes - manual metal arc, metal inert gas (MIG) and tungsten inert gas welding (TIG) – and most welding is on mild steel.</p> <p>In 2017, an IARC working group has determined that "sufficient evidence exists that welding fume is a human lung carcinogen (Group 1).</p> <p>A complicating factor in classifying welding fumes is its complexity. Generally, welding fume is a mixture of metal fumes (i.e., iron, manganese, chromium, nickel, silicon, titanium) and gases (i.e., carbon monoxide, ozone, argon, carbon dioxide). Welding fume can contain varying concentrations of individual components that are classified as human carcinogens, including hexavalent chrome and nickel. However the presence of such metals and the intensity of exposure to each differ significantly according to a number of variables, including the type of welding technique used and the composition of the base metal and consumable.</p> <p>WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS.</p> <p>Not available. Refer to individual constituents.</p> |
| ZINC OXIDE FUME | The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. |
| ZINC & TIN & TIN FUME | No significant acute toxicological data identified in literature search. |
| ZINC & BORIC ACID & ZINC OXIDE FUME | The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. |

| | | | |
|--|---|---------------------------------|---|
| Acute Toxicity | ✓ | Carcinogenicity | ✓ |
| Skin Irritation/Corrosion | ✗ | Reproductivity | ✗ |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity | ✗ | Aspiration Hazard | ✗ |

CIGWELD Comcoat C

Legend: ✗ – Data either not available or does not fill the criteria for classification
✔ – Data available to make classification

SECTION 12 Ecological information

Toxicity

| CIGWELD Comcoat C | Endpoint | Test Duration (hr) | Species | Value | Source |
|-------------------|---------------|--------------------|-------------------------------|---------------------|---------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| copper | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 48h | Fish | 0.00009mg/l | 4 |
| | EC50 | 96h | Algae or other aquatic plants | 0.03-0.058mg/l | 4 |
| | EC50 | 72h | Algae or other aquatic plants | 0.011-0.017mg/L | 4 |
| | LC50 | 96h | Fish | 0.0028mg/l | 2 |
| | EC50 | 48h | Crustacea | 0.0006-0.0017mg/l | 4 |
| zinc | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC10(ECx) | 168h | Algae or other aquatic plants | 0.0025mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 0.042mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | 0.005mg/l | 4 |
| | LC50 | 96h | Fish | 0.01068-0.01413mg/l | 4 |
| | EC50 | 48h | Crustacea | 0.06-0.08mg/l | 4 |
| tin | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 168h | Crustacea | <0.005mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | >0.0192mg/l | 2 |
| | LC50 | 96h | Fish | >0.0124mg/l | 2 |
| boric acid | Endpoint | Test Duration (hr) | Species | Value | Source |
| | LC50 | 96h | Fish | 70-80mg/l | 4 |
| | BCF | 672h | Fish | <3.2 | 7 |
| | EC50 | 72h | Algae or other aquatic plants | 40.2mg/l | 2 |
| | EC50 | 48h | Crustacea | 230mg/L | 5 |
| | NOEC(ECx) | 576h | Fish | 0.001mg/L | 5 |
| | EC50 | 96h | Algae or other aquatic plants | 15.4mg/l | 2 |
| sodium metaborate | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 768h | Fish | 0.1mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 15.4mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | 40mg/l | 2 |
| | LC50 | 96h | Fish | 66.4-83mg/l | 4 |
| welding fumes | Endpoint | Test Duration (hr) | Species | Value | Source |
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| copper fume | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 48h | Fish | 0.00009mg/l | 4 |
| | EC50 | 96h | Algae or other aquatic plants | 0.03-0.058mg/l | 4 |
| | EC50 | 72h | Algae or other aquatic plants | 0.011-0.017mg/L | 4 |
| | LC50 | 96h | Fish | 0.0028mg/l | 2 |
| | EC50 | 48h | Crustacea | 0.0006-0.0017mg/l | 4 |

Continued...

CIGWELD Comcoat C

| zinc oxide fume | Endpoint | Test Duration (hr) | Species | Value | Source |
|---|-----------|--------------------|-------------------------------|-----------------|--------|
| | BCF | 1344h | Fish | 19-110 | 7 |
| | LC50 | 96h | Fish | 0.112mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | 0.036-0.049mg/l | 4 |
| | EC50 | 48h | Crustacea | 0.105mg/l | 2 |
| | EC10(ECx) | 168h | Algae or other aquatic plants | 0.0025mg/l | 2 |
| | EC50 | 96h | Algae or other aquatic plants | 0.3mg/l | 2 |
| manganese fume | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 504h | Algae or other aquatic plants | 0.05-3.7mg/l | 4 |
| | EC50 | 72h | Algae or other aquatic plants | 2.8mg/l | 2 |
| | LC50 | 96h | Fish | >3.6mg/l | 2 |
| tin fume | Endpoint | Test Duration (hr) | Species | Value | Source |
| | NOEC(ECx) | 168h | Crustacea | <0.005mg/l | 2 |
| | EC50 | 72h | Algae or other aquatic plants | >0.0192mg/l | 2 |
| | LC50 | 96h | Fish | >0.0124mg/l | 2 |
| Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data | | | | | |

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------|-------------------------|------------------|
| boric acid | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|-----------------|-----------------|
| boric acid | LOW (BCF = 0) |
| zinc oxide fume | LOW (BCF = 217) |

Mobility in soil

| Ingredient | Mobility |
|------------|-------------------|
| boric acid | LOW (KOC = 35.04) |


SECTION 13 Disposal considerations

Waste treatment methods

| Product / Packaging disposal | <ul style="list-style-type: none"> Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill. |
|------------------------------|--|
|------------------------------|--|

SECTION 14 Transport information

Labels Required

| Marine Pollutant |  |
|------------------|---|
| HAZCHEM | Not Applicable |

Continued...

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|-------------------|---------------|
| copper | Not Available |
| zinc | Not Available |
| tin | Not Available |
| boric acid | Not Available |
| sodium metaborate | Not Available |
| welding fumes | Not Available |
| copper fume | Not Available |
| zinc oxide fume | Not Available |
| manganese fume | Not Available |
| tin fume | Not Available |

Transport in bulk in accordance with the ICG Code

| Product name | Ship Type |
|-------------------|---------------|
| copper | Not Available |
| zinc | Not Available |
| tin | Not Available |
| boric acid | Not Available |
| sodium metaborate | Not Available |
| welding fumes | Not Available |
| copper fume | Not Available |
| zinc oxide fume | Not Available |
| manganese fume | Not Available |
| tin fume | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

copper is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

zinc is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

tin is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

boric acid is found on the following regulatory lists

CIGWELD Comcoat C

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

sodium metaborate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

welding fumes is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

copper fume is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

zinc oxide fume is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

manganese fume is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

tin fume is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

National Inventory Status

| National Inventory | Status |
|---|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (copper; zinc; tin; boric acid; sodium metaborate; copper fume; zinc oxide fume; manganese fume; tin fume) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | No (copper; zinc; tin; copper fume; manganese fume; tin fume) |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | No (sodium metaborate) |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| Legend: | <p>Yes = All CAS declared ingredients are on the inventory</p> <p>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</p> |

Continued...

SECTION 16 Other information

| | |
|---------------|------------|
| Revision Date | 23/12/2022 |
| Initial Date | 08/11/2006 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|--|
| 6.1 | 01/11/2019 | One-off system update. NOTE: This may or may not change the GHS classification |
| 7.1 | 23/12/2022 | Classification review due to GHS Revision change. |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AII: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.