





HIGH PERFORMANCE WELDING CABLE



QUALITY CABLE FOR A PROFESSIONAL SETUP

QUALITY TESTED IN AUSTRALIA

The **Xtraflex** Welding Cable range provides the quality and high performance that is demanded from serious industrial workshop and site work operations.

FEATURES:

- Double Insulated for enhanced electrical safety and premium durability
- AS/NZS 1995:2003 Compliant that ensures premium suitability in the most demanding environments
- Ultra Flexible with High Abrasion Resistance for Xtreme durability and toughness
- Made from 100% Oxygen Free Copper (OFC) for superior conductivity and corrosion resistance ideal for Industrial Welding applications to keep production going round the clock!

Available in a wide range of cable sizes and lengths:

- **16mm²** (150m Spool)
- **25mm²** (150m Spool)
- **35mm**² (50m & 100m Spool)
- **50mm**² (50m & 100m Spool)
- **70mm²** (50m & 100m Spool)
- **95mm²** (50m & 100m Spool)

CABLE MARKED:

Cable Size

Standards

Part No.

Meter Reading

CIGWELD XTRAFLEX WELDING CABLE 50 SQMM AS1995 CW7901223 MTR-0001









Choose the right welding cable to suit your application

Part No	Core Diameter	Current Rating	Duty Cycle	Voltage	Spool Size	Barcode
CW7901220	16mm²	225A	30% @ 40°C	600V DC	150m	9 310574 082724 >
CW7901221	25mm²	300A	30% @ 40°C	600V DC	150m	9 "310574" 082731">
CW7901271	35mm²	375A	30% @ 40°C	600V DC	50m	9 310574 082755 >
CW7901222	35mm²	375A	30% @ 40°C	600V DC	100m	9 310574 082748 >
CW7901272	50mm²	475A	30% @ 40°C	600V DC	50m	9 310574 082779 >
CW7901223	50mm²	475A	30% @ 40°C	600V DC	100m	9 310574 082762 >
CW7901224	70mm²	590A	30% @ 40°C	600V DC	50m	9 310574 082786 >
CW7901273	70mm²	590A	30% @ 40°C	600V DC	100m	9 310574 082793 >
CW7901225	95mm²	715A	30% @ 40°C	600V DC	50m	9 310574 082809">
CW7901274	95mm²	715A	30% @ 40°C	600V DC	100m	9 310574 082816 >







