

Nozzles & Nozzle Insulators - Flat Arc Spot Style Air-Cooled

FAS Series

Self Insulated Nozzles.

2 per pack



21-62FAS

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Thread-On	1/2" (12.7 mm)	21-62FAS	1210-1520	--	--

FAS Series

Use with Nozzle Insulator Part No. 34A (Stock No. 1340-1100).

2 per pack



24A-100FAS



34A Insulator
(sold separately)

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Slip-On	3/4" (19.5 mm)	24A-100FAS	1240-1550	--	--

FAS Series

Use with Nozzle Insulator Part No. 35CT (Stock No. 1350-1400).

2 per pack



25CT-162FAS



35CT Insulator
(sold separately)

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Thread-On	1-5/8" (41.3 mm)	25CT-162FAS	1250-1570	--	--

Nozzles - Eliminator® Style Air-Cooled

EL22I Series

3-Piece Nozzle Design - 0.875" (22.2 mm) Outside Diameter

Self Insulated Nozzles. Use with Part No. EL52 (Stock No. 1560-1110) Gas Diffuser.

2 per pack



EL22I Series

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Slip-On	3/8" (9.5 mm)	EL22I-37	1260-1601	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	1/2" (12.7 mm)	EL22I-50	1260-1602	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	1/2" (12.7 mm)	EL22I-50P	1260-1686	Standard	5/32" (3.97 mm) Tip Protruding
	5/8" (15.9 mm)	EL22I-62	1260-1603	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/4" (19.5 mm)	EL22I-75	1260-1604	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess

EL22CT Series

3-Piece Nozzle Design - 0.875" (22.2 mm) Outside Diameter

Self Insulated Nozzles. Use with Part No. EL52CT Series Gas Diffuser.

2 per pack



EL22CT Series

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Thread-On	3/8" (9.5 mm)	EL22CT-37	1260-1625	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/8" (9.5 mm)	EL22CT-37F	1260-1635	Standard	Flush To 1/16" (1.6 mm) Tip Recess
	1/2" (12.7 mm)	EL22CT-50	1260-1626	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	1/2" (12.7 mm)	EL22CT-50F	1260-1636	Standard	Flush To 1/16" (1.6 mm) Tip Recess
	5/8" (15.9 mm)	EL22CT-62	1260-1627	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	5/8" (15.9 mm)	EL22CT-62F	1260-1637	Standard	Flush To 1/16" (1.6 mm) Tip Recess
	5/8" (15.9 mm)	EL22CT-62P	1260-1692	Standard	5/32" (3.97 mm) Tip Protruding
	5/8" (15.9 mm)	EL22CT-62H	1260-1629	Standard, Heavy Duty	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/4" (19.5 mm)	EL22CT-75	1260-1628	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess

Nozzles - Eliminator® Style Air-Cooled

EL24I Series

3-Piece Nozzle Design - 0.875" (22.2 mm) Outside Diameter
 Self Insulated Nozzles. Use with Part No. EL54 Series Gas Diffusers.
 2 per pack



EL24I Series

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Slip-On	3/8" (9.5 mm)	EL24I-37	1260-1606	Tapered	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	1/2" (12.7 mm)	EL24I-50	1260-1607	Tapered	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	5/8" (15.9 mm)	EL24I-62	1260-1608	Tapered	Flush To 1/16" (1.6 mm) Tip Recess
	5/8" (15.9 mm)	EL24I-62R	1260-1677	Tapered	3/8" (9.5 mm) Tip Recess
	5/8" (15.9 mm)	EL24I-62H	1260-1631	Tapered, Heavy Duty	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/4" (19.5 mm)	EL24I-75	1260-1609	Tapered	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/4" (19.5 mm)	EL24I-75H	1260-1632	Tapered, Heavy Duty	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess

EL24CT Series

3-Piece Nozzle Design - 0.875" (22.2 mm) Outside Diameter
 Self Insulated Nozzles. Use with Part No. EL52CT Series Gas Diffusers.
 2 per pack



EL24CT Series

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Thread-On	3/8" (9.5 mm)	EL24CT-37	1260-1650	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	1/2" (12.7 mm)	EL24CT-50	1260-1651	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	1/2" (12.7 mm)	EL24CT-50P	1260-1701	Standard	5/32" (3.97 mm) Tip Protruding
	5/8" (15.9 mm)	EL24CT-62	1260-1652	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	5/8" (15.9 mm)	EL24CT-62F	1260-1667	Standard	Flush To 1/16" (1.6 mm) Tip Recess
	5/8" (15.9 mm)	EL24CT-62R	1260-1682	Standard	3/8" (9.5 mm) Tip Recess
	5/8" (15.9 mm)	EL24CT-62H	1260-1657	Standard, Heavy Duty	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/4" (19.5 mm)	EL24CT-75	1260-1653	Standard	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess
	3/4" (19.5 mm)	EL24CT-75H	1260-1658	Standard, Heavy Duty	1/8" - 5/32" (3.2 mm - 3.97 mm) Tip Recess

REL24 Series

3-Piece Nozzle Design - 1.000" (25.4 mm) Outside Diameter
 Self Insulated Nozzles. Nickel plated nozzle. Use with Part No. QTR56-SW Gas Diffuser.
 2 per pack



REL24 Series

Nozzle Style	Bore Diameter	Part No.	Stock No.	Nozzle Design	Nozzle/Contact Tip Relationship
Thread-On	1/2" (12.7 mm)	REL24CT-50	1240-1305	Straight	5/32" (3.97 mm) Tip Recess
	1/2" (12.7 mm)	REL24CT-50F	1240-1315	Straight	Flush To 1/16" (1.6 mm) Tip Recess
	1/2" (12.7 mm)	REL24CT-50P	1240-1310	Straight	5/32" (3.97 mm) Tip Protruding
	5/8" (15.9 mm)	REL24CT-62	1240-1306	Straight	5/32" (3.97 mm) Tip Recess
	5/8" (15.9 mm)	REL24CT-62F	1240-1316	Straight	Flush To 1/16" (1.6 mm) Tip Recess
	5/8" (15.9 mm)	REL24CT-62P	1240-1311	Straight	5/32" (3.97 mm) Tip Recess
	3/4" (19.5 mm)	REL24CT-75F	1240-1317	Straight	Flush To 1/16" (1.6 mm) Tip Recess
	3/4" (19.5 mm)	REL24CT-75P	1240-1312	Straight	5/32" (3.97 mm) Tip Protruding